



DESCRIPTION

PLASTIC INJECTION MOLDED ADJUSTMENT RING

MOLDED FROM HIGH DENSITY POLYETHYLENE AS DEFINED IN ASTM SPECIFICATION D1248

ACTUAL RESIN PROPERTIES WILL VARY ALLOWING FOR THE UTILIZATION OF A MAXIMUM PERCENT OF RECYCLED MATERIAL

THE PERCENT OF POST CONSUMER WASTE TO INDUSTRIAL WASTE WILL VARY WITH AVAILABILITY AND PROPERTY RETENTION NEEDS

COLOR, SHADE AND UNIFORMITY WILL VARY WITH THE MIX OF THE POST CONSUMER AND INDUSTRIAL WASTE MATERIALS

DIMENSIONS SHOWN ARE NOMINAL - ACTUAL SIZE WILL VARY WITHIN ALLOWABLE TOLERANCE AND REQUIRED FIT

DIMENSION SCHEDULE (inches)

CONE SIZE	DIM A	DIM B	DIM C	DIM D	DIM H1 - H2
24	23.75	33.50	5.00	23.25	.75 1.50
27	26.75	36.50	5.00	26.25	.75 1.50
30	29.75	39.50	5.00	29.25	1.50 2.25
32	31.75	41.50	5.00	31.25	1.25 2.25
34	33.75	41.50	4.00	33.25	1.25 2.25

APPROVAL DATE _____	DESCRIPTION	SPECIFICATION REFERENCE	STANDARD PLATE NO.
BY _____	POLYETHYLENE MANHOLE ADJUSTMENT RING SLOPE DESIGN		